

# Fractured dirt: Deformation textures and processes in sediment and other unconsolidated deposits

James P. Evans and Kelly Keighley Bradbury

*Department of Geology, Utah State University, Logan, Utah 84322-4505, USA*

Structural geologists examine rock deformation to evaluate how Earth's crust responds to tectonic loads in the brittle, mixed mode (or the schizosphere of Scholz, 2002) and plastic regimes of the crust (Rutter, 1986). Recently, some researchers have turned their attention to unconsolidated and nonlithified deposits, elucidating how materials in the near-surface regime deform, and how the impact of this deformation may be felt in a variety of settings (Maltman, 1988; Rawling et al., 2001; Cashman et al., 2007, p. 611 of this issue).

The nature of exhumed fault-related rocks along the San Andreas fault and other faults has been examined for over 70 yr (Waters and Campbell, 1935), and for the most part, work has focused on exhumed fault rock in bedrock (Anderson et al., 1980; Chester and Logan, 1986; Chester et al., 1993; Wibberley and Shimamoto, 2003; Faulkner et al., 2003; Jeffries et al., 2006; Dor et al., 2006). These types of studies evaluate the processes at seismogenic depths where seismic energy is radiated (Scholz, 2002). Within the upper several kilometers, however, faults, while not radiating energy, transmit energy and displacement to Earth's surface, and this may pose significant hazards (Spudich and Olsen, 2001). Developing greater insights into the processes within fault zones in the upper 0–500 m of Earth's surface has important implications for hazards analysis, zoning, and paleoseismic studies. The ability to identify the textures in near-surface portions of faults that indicate whether a fault ruptures seismically, or fails by slow slip or creep, would be an important tool for paleoseismologists and structural geologists.

Cashman et al. document deformation in near-surface exposures of the San Andreas fault, and address two emerging topics: deformation in faults at the surface, and more generally, deformation processes in poorly lithified deposits prior to burial and diagenesis. Cashman et al. show that the microstructures of deformed sand in a creeping portion of the San Andreas fault reflect distributed deformation, and preserve no deformation bands, whereas siltstones and sandstones along a seismogenic portion of the fault exhibit deformation bands, which were the product of grain fracture and crushing. Cashman et al. indicate that the presence of brittle, localized slip in deformation bands may be an indicator of past rapid failure. If so, this would be an important finding, as few rock structures unequivocally document seismic slip (Cowan, 1999). Cashman et al. suggest that the behavior of the sediments at the seismic slip site can be explained in the context of the "grain bridge" model, in which stresses at grain boundaries fail under the concentrated stresses at the grain contact points (Gallagher et al., 1974; Sammis and Steacy, 1994; Morgan and Boettcher, 1999). The distributed deformation along the creeping segment lacks deformation bands, and fabrics within the multiple slip surfaces exhibit a grain-preferred orientation that may be the result of slow slip. Expanding these results to recent drilling of seismically ruptured faults (Ma et al., 2006; Sone et al., 2007) and other studies of shallow fault-related rocks (Dor et al., 2006) may provide significantly new insight into the processes that transmit seismic slip to Earth's surface along either very narrow slip zones or across zones 10–50 m wide.

Experimental verification of these results may be obtained from recent rock-on-rock friction experiments with gouge layers, deformed at normal stress values of 1–50 Mpa (Biegel et al., 1989; Anthony and

Marone, 2005; Knuth and Marone, 2007). But, due to the strain rates needed to replicate co-seismic rupture velocities, and the difficulty in imaging deformed unconsolidated sediment, it will be challenging to evaluate the microscopic deformation mechanisms at most experimental conditions that approximate field conditions. Low confining pressure ( $P_c$ ) experiments are typically the domain of geotechnical engineers, who have produced strain localization in sand at  $P_c$  of 10's to 100's kPa, and for a variety of material types (Finno et al., 1997; Alshibli et al., 2003). One of the interesting results from these experiments is that shear band localization in sand is suppressed by increasing  $P_c$ , and the geometry of the load conditions are important for determining how strain is localized. Experiments can also examine the impact of gouge thickness and particle characteristics. Anthony and Marone (2005) showed that smooth grains deform by grain boundary sliding, whereas rough grains roll and dilate. In addition, stick-slip behavior is promoted by the presence of smooth grains. Knuth and Marone (2007) further documented the importance of grain material properties on the behavior of faults.

The other important aspect of Cashman et al.'s work is that it draws attention to the analysis of brittle deformation of nonlithified deposits. This has implications not only for earthquake studies but for hydrology, ground failure, deformation of saturated sediments in subaqueous and subareal settings, and ultimately for interpreting deformed rock (Maltman, 1988; Cashman and Cashman, 2000; Rawling et al., 2001; Du Bernard et al., 2002; Rawling and Goodwin, 2003; Bhattacharya and Davies, 2004; Evans and Bradbury, 2004; Wilson et al., 2003; Schultz and Siddharthan, 2005; Aydin et al., 2006; Kirby et al., 2007). These researchers have documented that materials with little or no cohesive strength and, in some cases, with extremely high porosities, may sustain brittle slip localization, cataclasis, and dilatant fracturing.

The mechanics of deformation in these conditions has been elegantly described by Wong et al. (2004), Schultz and Siddharthan (2005), and Aydin et al. (2006). Instead of using the Mohr-Coulomb space familiar to most geologists, the deformation of unconsolidated porous deposits and rock can be examined with a yield analysis, where failure may occur by dilatency, shearing on localized surfaces, compaction, or distributed flow. Prediction of the mode of deformation depends on the relationships between differential stress ( $\sigma_1 - \sigma_3$ ) and the mean stress [ $(\sigma_1 + \sigma_2 + \sigma_3)/3$ ], as well as on grain properties, porosity, and water content. In this context, the style of deformation over a range of conditions can be predicted, and field and experimental observations confirm these predictions (Schultz and Siddharthan, 2005; Aydin et al., 2006).

The mode by which nonlithified materials deform is an increasingly important topic for geologists to consider, as such deformation has impacts on human-related activities such as groundwater resource development, waste isolation, and deep engineered structures. The implications for the rock record are also significant, because we must allow for the possibility that some of the brittle deformation we observe in rock may have developed before lithification. The analyses by Cashman et al., Cashman and Cashman (2000), and others cited above suggest that we might want to revise our conventional structural approach to examining deformed rocks, and admit the possibility of fracture, flow, and shearing in the nonlithified state.

## REFERENCES CITED

- Alshibli, K.A., Batiste, S.N., and Sture, S., 2003, Strain localization in sand: Plane strain versus triaxial compression: *Journal of Geotechnical and Geoenvironmental Engineering*, v. 129, p. 483–494, doi: 10.1061/(ASCE)1090-0241(2003)129:6(483).
- Anderson, J.L., Osborne, R.H., and Palmer, D.F., 1980, Petrogenesis of cataclastic rocks within the San Andreas fault zone of southern California: *Tectonophysics*, v. 67, p. 221–249, doi: 10.1016/0040-1951(80)90269-3.
- Anthony, J.L., and Marone, C., 2005, Influence of particle characteristics on granular friction: *Journal of Geophysical Research*, v. 110, doi: 10.1029/2004JB003399, doi: 10.1029/2004JB003399.
- Aydin, A., Borja, R.I., and Eichhubl, P., 2006, Geological and mathematical framework for failure modes in granular rock: *Journal of Structural Geology*, v. 28, p. 83–99, doi: 10.1016/j.jsg.2005.07.008.
- Bhattacharya, J.P., and Davies, R., 2004, Sedimentology and structure of growth faults at the base of the Ferron Sandstone Member along Muddy Creek, Utah, in Chidsey, T.C., Jr., et al., eds., *Regional to wellbore analog for fluvial-deltaic reservoir modeling: the Ferron Sandstone of Utah*: American Association of Petroleum Geologists Studies in Geology, v. 50, p. 279–304.
- Biegel, R.L., Sammis, C.G., and Dieterich, J.H., 1989, The frictional properties of a simulated gouge having a fractal particle size distribution: *Journal of Structural Geology*, v. 11, p. 827–846, doi: 10.1016/0191-8141(89)90101-6.
- Cashman, S.M., and Cashman, K.V., 2000, Cataclasis and deformation-band formation in unconsolidated marine terrace sand, Humboldt County, California: *Geology*, v. 28, p. 111–114, doi: 10.1130/0091-7613(2000)28<111:CADFIU>2.0.CO;2.
- Cashman, S.M., Baldwin, J.N., Casman, K.V., Swanson, K., and Crawford, R., 2007, Microstructures developed by coseismic and aseismic faulting in near-surface sediments, San Andreas fault, California: *Geology*, v. 35, p. 611–614, doi: 10.1130/G23545A.1.
- Chester, F.M., and Logan, J.M., 1986, Implications for mechanical properties of brittle faults from observation of the Punchbowl fault zone, California: *Pure and Applied Geophysics*, v. 124, p. 79–106, doi: 10.1007/BF00875720.
- Chester, F.M., Evans, J.P., and Biegel, R.L., 1993, Internal structure and weakening mechanisms of the San Andreas Fault: *Journal of Geophysical Research*, v. 93, p. 771–786.
- Cowan, D.S., 1999, Do faults preserve a record of seismic slip? A field geologist's opinion: *Journal of Structural Geology*, v. 21, p. 995–1001, doi: 10.1016/S0191-8141(99)00046-2.
- Dor, O., Ben-Zion, Y., Rockwell, T., and Brune, J., 2006, Pulverized rocks in the Mojave segment of the San Andreas fault: *Earth and Planetary Science Letters*, v. 245, p. 642–654, doi: 10.1016/j.epsl.2006.03.034.
- Du Bernard, X., Eichhubl, P., and Aydin, A., 2002, Dilation bands: A new form of localized failure in granular media: *Geophysical Research Letters*, v. 29, doi: 10.1029/2002GL015966.
- Evans, J.P., and Bradbury, K.E.K., 2004, Deformation of non-welded Bishop tuff, Eastern California: Processes and impact on fluid flow in the unsaturated zone: *Vadose Zone Journal*, v. 3, p. 602–623.
- Faulkner, D.C., Lewis, A.C., and Rutter, E.H., 2003, On the internal structure and mechanics of large strike-slip fault zones; Field observations of the Carboneras Fault in southeastern Spain: *Tectonophysics*, v. 367, p. 235–251, doi: 10.1016/S0040-1951(03)00134-3.
- Finno, R.J., Harris, W.W., Mooney, M.A., and Viggiani, G., 1997, Shear bands in plane strain compression of loose sand: *Geotechnique*, v. 47, p. 149–165.
- Gallagher, J.J., Friedman, M., Handin, J., and Sowers, G.M., 1974, Experimental studies relating to microfracture in sandstone: *Tectonophysics*, v. 21, p. 203–247, doi: 10.1016/0040-1951(74)90053-5.
- Jefferies, S.P., Holdsworth, R.E., Wibberley, C.A.J., Shimamoto, T., Spiers, C.J., Niemeijer, A.R., and Lloyd, G.E., 2006, The nature and importance of phyllonite development in crustal-scale fault cores: An example from the Median Tectonic Line: *Japanese Journal of Structural Geology*, v. 28, p. 220–235, doi: 10.1016/j.jsg.2005.10.008.
- Kirby, S.M., Janecke, S.U., Dorsey, R.J., Housen, B.A., McDougall, K., Langenheim, V., and Stealy, A., 2007, Pleistocene Brawley and Ocotillo formations: Evidence for initial strike-slip deformation along the San Felipe and San Jacinto fault zones, California: *The Journal of Geology*, v. 115, p. 43–62, doi: 10.1086/509248.
- Knuth, M., and Marone, C., 2007, Friction of sheared granular layers: Role of particle dimensionality, surface roughness, and material properties: *Geochemistry, Geophysics: Geosystems*, v. 8, p. Q03012, doi: 10.1029/2006GC001327.
- Ma, K.-F., Tanaka, H., Song, S., Wang, C., Hung, J., Song, Y., Yeh, E., Soh, W., Sone, H., Kuo, L., and Wu, H., 2006, Slip zone and energetics of a large earthquake from the Taiwan Chelungpu fault drilling project: *Nature*, v. 444, p. 473–476, doi: 10.1038/nature05253.
- Maltan, A.J., 1988, The importance of shear zones in naturally deformed wet sediments: *Tectonophysics*, v. 145, p. 163–175, doi: 10.1016/0040-1951(88)90324-1.
- Morgan, J.K., and Boettcher, M.S., 1999, Numerical simulations of granular shear zones using the distinct element method 1: Shear zone kinematics and the micromechanics of localization: *Journal of Geophysical Research*, v. 104, p. 2703–2719, doi: 10.1029/1998JB900056.
- Rawling, G.C., Goodwin, L.B., and Wilson, J.L., 2001, Internal architecture, permeability structure, and hydrologic significance of contrasting fault zone types: *Geology*, v. 29, p. 43–46, doi: 10.1130/0091-7613(2001)029<0043:IAPSAH>2.0.CO;2.
- Rawling, G.C., and Goodwin, L.B., 2003, Cataclasis and particulate flow in faulted, poorly-lithified sediments: *Journal of Structural Geology*, v. 25, p. 317–331, doi: 10.1016/S0191-8141(02)00041-X.
- Rutter, E.H., 1986, On the nomenclature and mode of failure transitions in rock: *Tectonophysics*, v. 122, p. 381–387, doi: 10.1016/0040-1951(86)90153-8.
- Sammis, C.G., and Steacy, S.J., 1994, The micromechanics of friction in a granular layer: *Pure and Applied Geophysics*, v. 142, p. 777–794, doi: 10.1007/BF00876064.
- Scholz, C.H., 2002, *The Mechanics of Earthquakes and Faulting*: Cambridge, UK, Cambridge University Press, 471 p.
- Schultz, R.A., and Siddharthan, R., 2005, A general framework for the occurrence and faulting of deformation bands in porous granular rocks: *Tectonophysics*, v. 411, p. 1–18, doi: 10.1016/j.tecto.2005.07.008.
- Sone, H., Yeh, E., Nakaya, T., Hung, J., Ma, K., Wang, C., Song, S., and Shimamoto, T., 2007, Mesoscopic structural observations of cores from the Chelungpu fault system, Taiwan Chelungpu fault drilling project Hole A, Taiwan: *Terrestrial, Atmospheric, and Ocean Sciences*, (in press).
- Spudich, P., and Olsen, K.B., 2001, Fault zone amplified waves as a possible seismic hazard along the Calaveras Fault in Central California: *Geophysical Research Letters*, v. 28, p. 2533–2536, doi: 10.1029/2000GL011902.
- Waters, A.C., and Campbell, C.D., 1935, Mylonites from the San Andreas fault zone: *American Journal of Science*, v. 24, p. 473–503.
- Wibberley, C.A.J., and Shimamoto, T., 2003, Internal structure and permeability of major strike-slip fault zones: The Median Tectonic Line in Mie Prefecture, southwest Japan: *Journal of Structural Geology*, v. 25, p. 59–78, doi: 10.1016/S0191-8141(02)00014-7.
- Wilson, J.E., Goodwin, L.B., and Lewis, C.J., 2003, Deformation bands in non-welded ignimbrites: Petrophysical controls on fault zone deformation and evidence for preferential fluid flow: *Geology*, v. 31, p. 837–840, doi: 10.1130/G19667R.1.
- Wong, T.-F., David, C., and Menendez, B., 2004, *Mechanical compaction, in Gueguen, Y., and Bouteca, M., eds., Mechanics of Fluid Saturated Rocks*: Amsterdam, Elsevier, p. 55–114.

Printed in USA